

BRTN30WSS5PC Technical Specifications																		
Power source (KVA)	Power Supply (V)	Recommended IMM (T)	Traverser Stroke	Traverser Stroke (mm)	Crosswise Stroke (mm)	Vertical Stroke (mm)	Stand-by station (mm)	Max loading (Kg)	Cycle time (s)	Dry take out time(s)	Arm model	Model of EOAT	Angel	Working air pressure (MPa)	Air consumption (N-l /cycle)	Positioning accuracy (mm)	Complete machine size (mm)	Net weight (Kg)
6.7	220	2200-4000	AC servo motor	4000	2500	3000	295	60	36.5	9.05	Single arms and telescopic type	4 suction 2 fixtures	C axis: 180° A axis: 360°	0.5-0.6	47	±0.1	5333*3755.5*2983	2020
transverse				Crosswise					Obverse arm					Deputy arm				
Transverse electrical machines	Reducer	Slide rail	Gear rack / Belt	Electrical machines	Reducer	Slide rail	Gear rack / Belt	air cylinder	Electrical machines	Reducer	Slide rail	Gear rack / Belt	Air cylinder	electrical machines	Reducer	Slide rail	Gear rack /Belt	Air cylinder
1300w	1500W 1: 9	30mm	gear rack:- 29mm	1300W	1500W 1:9	30mm	gear rack: 29mm	\	1800W	2000W 1:15	25mm 30mm	Belt: 50mm gear rack: 30mm	50-1550	\	\	\	\	\

